

HOW TO APPLY CUTEK® QUICKCLEAN



A SIMPLE STEP-BY-STEP GUIDE

1 PROTECT AND TEST

Protect adjacent surfaces, vegetation, vehicles and pedestrian areas. Test a small section first to confirm the dilution and cleaning method are suitable for the surface.

2 DILUTE WITH WATER

Dilute approximately one part CUTEK® Quickclean with eight parts water. The required strength may vary depending on the surface and level of dirt, grease or grime.

3 WET THE SURFACE

Thoroughly wet the surface with clean water before applying CUTEK® Quickclean. This helps the diluted cleaner spread evenly and work effectively.

4 APPLY AND ALLOW TO WORK

Apply liberally using a brush, roller, broom or low-pressure garden sprayer. Leave for 5–15 minutes, depending on the level of build-up. Scrub stubborn areas with a stiff fiber brush.

5 RINSE THOROUGHLY

Rinse thoroughly with clean water, working from the highest point down in the direction of the grain. Allow wood to dry completely before applying CUTEK® Extreme.



For best results, use a pressure washer at approximately 750 psi with a fan jet. Adjust the pressure or working distance to avoid damaging the wood fibers. Never use a turbo nozzle on wood.

- ✓ **ALWAYS DILUTE:** CUTEK® Quickclean is a concentrated exterior exterior cleaner.
- ✓ **IDEAL FOR MAINTENANCE:** Use before applying a maintenance coat of CUTEK® Extreme.
- ✓ **CLEAN YOUR EQUIPMENT:** Brushes, rollers and equipment can be cleaned with water after use.

WATCH OUR VIDEO TUTORIAL

Use this step-by-step video as an additional resource to guide you through using CUTEK® Quickclean.

Follow the practical demonstration and expert tips to correctly dilute, apply and rinse the cleaner without damaging the wood.

Thorough cleaning removes dirt, grease and grime, preparing the wood for simple ongoing maintenance.

