

HOW TO APPLY CUTEK® WOOD REVIVER



A SIMPLE STEP-BY-STEP GUIDE

1 PROTECT AND TEST

Protect adjacent surfaces, vegetation, vehicles and pedestrian areas. Test a small section first to determine the required dilution, working time and amount of product.

2 PREPARE THE PRODUCT

CUTEK® Wood Reviver can be used diluted or undiluted depending on the wood and severity of weathering or staining. Use your test area to determine the appropriate strength.

3 WET AND APPLY

Thoroughly wet the wood with clean water. Apply CUTEK® Wood Reviver liberally using a brush, roller, broom or low-pressure garden sprayer.

4 ALLOW TO WORK

Leave the product on the wood for 1-8 hours, depending on the severity of staining or discoloration. Moderately scrub stubborn areas with a stiff fiber brush if required.

5 PRESSURE RINSE

Rinse thoroughly using a pressure washer at approximately 750 psi with a fan jet. Work from the highest point down, following the grain, until there is minimal or no sudsing.



A garden hose is not sufficient to remove CUTEK® Wood Reviver. Adjust the pressure or working distance to avoid damaging the wood fibers. Go along the grain, not across it and never use a turbo nozzle

✓ **DOES NOT STRIP OLD COATINGS:** Remove existing coatings with CUTEK® Wood Stripper first.

✓ **ALLOW TO DRY:** Wood must be completely dry before applying CUTEK® Extreme.

WATCH OUR VIDEO TUTORIAL

Use this step-by-step video as an additional resource to guide you through using CUTEK® Wood Reviver.

Follow the practical demonstration and expert tips to correctly restore weathered, grayed or stained wood and prepare it for protection.

Correct application and thorough rinsing help reveal the wood's natural color and grain before applying CUTEK® Extreme.

